

SAP E & C CALIBRATION OF THERMOCOUPLE, RTD SETUP
i.e. CHARACTERISTICS OF TEMPERATURE SENSOR SETUP
(PRODUCT CODE: SAP - 32)



The **Calibration of Thermocouple, RTD setup (SAP – 32)** gives an idea regarding calibration procedure for temperature transducers such as RTD, Thermocouple & Thermistors.

Calibration of Thermocouple, RTD setup (SAP – 32)

Technical Specification: -

No.	Technical Specifications
1	Temperature range: 0-500°C
2	Calibration facility for thermocouple & RTD
3	7-segment LED display for temperature Indicator controller
4	Test point for Thermister, RTD (Resistance Measurement).
5	Test point for voltage measurement for Thermocouple.
6	3-½-digit display.
7	Muffle furnace with insertion points for RTD, THERMOCOUPLE and THERMISTER

Range of Experiments-

- ❖ Study of Calibration of RTD, Thermistors and Thermocouple

Features: -

- ❖ Compact Ergonomic Design.
- ❖ User Friendly, Self Explanatory Systems.
- ❖ Robust Construction.
- ❖ Enhanced Electrical Safety Considerations.
- ❖ Training Manuals & Mimic Charts for Operation Ease.
- ❖ Inbuilt Safety Measures to avoid improper usage.

System Dimensions- 4Ft. (L) X 2 Ft. (W) X 4 Ft. (H)

Services Required-

- ❖ Electric Supply of 1φ 230 VAC.

Note-

All descriptive matter and illustrations are intended to give only a general idea of the equipment detailed specifications may be altered at the company's discretion without any notice.

Manufactured/Marketed By
SAP ENGINEERS & CONSULTANTS

Regd. Off. : Shop No. 26-27,'Srushti', Survey No.82, Near Guru Ganesh Nagar,
Eklavya College Road (D.P.Road), Kothrud, Pune - 411 038


Telephone : (020) 2538 4737

Mobile : 94220 88946, 95524 75082

Fax : (020) 2538 3544

Email : pravinsdeode@vsnl.net, sapengineerspune@gmail.com

Website : www.sapengineers.com / www.sapengineers.co.in



For More Details Visit Our Website At: www.sapengineers.com, E-mail:- pravinsdeode@vsnl.net
 SAP Engineers & Consultants, Kothrud, Pune-411 038. Ph-(020)25384737